


H.265 3MP HD-IP IR Dome Camera



Features

- 1/3" Panasonic Sensor
- 3MP Camera
- Max. resolution: 2304(H) x 1296(V)
- ICR auto switch, true day / night
- 3D DNR
- Supports smart analysis of valuables watching, perimeter and abnormal video signal detection
- Supports defogging, HLC, BLC, digital image stabilization and defect correction to fit different needs
- Supports CVBS
- Support smart phone, iPad, remote monitoring

Specifications

Model	IP-5IRD3002-2.8
Camera	
Image Sensor	1 / 3 "CMOS
Effective Pixels	2304 x 1296
Electronic Shutter	1/25s~ 1/100000s
Min. Illumination	Color:0.05lux@F1.2,AGC ON B/W:0lux with IR
Lens	2.8mm Fixed Lens
Lens Angle	Horizontal: 50°
WDR	DWDR
BLC	Yes
DNR	2D/3D DNR
Image	
Video Compression	H.265 MP, H.264 BL/MP/HP, MJPEG
Audio Compression	G.711A/G.711U
Bit-rate	64Kbps ~ 10Mbps
Encode Mode	VBR/CBR
Image Quality	Five Levels under VBR: Freely adjustable under CBR
Resolution	3MP (2304x1296) , 1080P (1920x1080) , 720P (1280x720) , D1, CIF, 480x240
Video Frame Rate	3MP (1~30fps) / 1920x1080 (1~30fps) / 720P (1~30fps) 720P (1~30fps) / D1 (1~30fps) / CIF (1~30fps) D1 (1~30fps) / 480x240 (1~30fps) / CIF (1~30fps)
Image Setting	ROI, Saturation, Brightness, Hue, Contrast,WDR, Sharpness, DNR, etc
Port	
Network	RJ45
Video output	CVBS (BNC x 1)
Audio	one-way audio (MIC IN x 1)
Card Storage	N/A
RS485	N/A
Alarm In / Out	N/A
Function	
Remote Monitoring	Browser, CMS ,mobile app
Supported Browsers	IE / Chrome / Firefox / Safari
Online Connection	10 online users
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, SMTP, FTP
Connection Protocol	ONVIF
Storage	network remote storage
Smart Alarm	Motion Alarm
Intelligent Analysis	PEA/OSC/AVD
Day & Night	ICR
IR Distance	20~30m
IR LED - count	2 (array led 28mil)
Water-proof	IP66
Others	
Angle Adjustment	horizontal:0°~360°, vertical: 0°~90°, rotation: 0°~360°
Power Supply	DC 12V/PoE
Power Consumption	< 2.5W (IR Off) / < 5W (IR On)
Working Environment	-20°C ~ 50°C , 10% ~ 90% Humidity
Dimension & Weight	Φ109mmx130mm / ≈689g