

FEATURE

- 1/3" 3Mp CMOS Lens
- Recording: 30fps
- 3DNR, DWDR, ICR
- 2.8~12mm Vari-Focal Lens
- 2 Super IR; Distance: 65 ~ 98ft
- ONVIF, GB-T/28181-2011
- Weatherproof; DC 12V / PoE



IP-IRD3002VF-G-2812

IP-IRD3002VF-W-2812

SPECIFICATION

Camera	Image Sensor	1/3 " CMOS Sensor ; 2048 ×1536
	Electronic Shutter	1/25s~1/100000s
	Min. Illumination	0 Lux (IR ON)
	Lens & Auto Iris	2.8~12mm Vari-Focal Lens ; Fixed Iris
	Day-Night Switch	ICR auto switch
	WDR & DNR	Digital WDR ; 3D noise reduction
Image	Encode Mode	VBR/CBR
	Image Quality & Bitrate	Five levels VBR; Freely adjustable under CBR ; 64Kbps~8Mbps
	Resolution	3MP(2048 × 1536)、 1080P(1920 × 1080), 720P(1280 × 720), D1, CIF, 480 x240 3MP (1~30fps) /1920×1080 (1~30fps)
	Multi-streams	1280 ×720 (1~10fps) /D1 (1~30fps) /CIF (1~30fps) CIF (1~30fps) /480 ×240 (1~30fps)
	Image Settings	Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR., etc., adjustable through client software or web browser
Interface	ROI	Support
	Network	RJ45
	Audio	MIC IN ×1
Function	Remote Monitoring	IE browsing, CMS remote control
	Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	Interface Protocol	ONVIF, GB-T/28181-2011
	Storage & Alarm	Network remote storage ; Motion Alarm
	IR Distance	65 ~ 98 ft. (20 ~ 30 m); 2 Super IR
	Water-proof	IP66
Others	Power Supply	DC 12V / PoE ; < 3.5W (ICR OFF); < 6 W (ICR ON)
	Working Environment	-40°F ~ 122°F (-40°C~50°C), 10%~90% humidity
	Dimension & Weight	4.3" x 5.1" (109mm ×130mm) ; 1.7lbs (751g)

WEST OFFICE (CA)

110 California Ave., City of Industry, CA91744
TEL: 626-961-8810 FAX: 626-961-8809

HEADQUARTERS

50 Commercial Street, Plainview, NY 11803
TEL: 516-870-3779 FAX: 516-390-1200

EAST OFFICE (NY)

129-04 14th Ave., College Point, NY 11356
TEL: 718-939-2710 FAX: 718-939-2713